Product Features and Benefits

- Combination safety/ solar control window film
- Help protect from broken glass hazards
- Increase privacy, reduce glare and eye discomfort
- Increase comfort and reduce air conditioning costs
- Helps extend the life of furnishings by significantly reducing harmful UV rays

Applications

- Bomb Blast Protection
- Building Envelope Protection
- Helping to Deter Break & Entry
- Safety Glazing
- Spontaneous Glass Breakage
- Seismic Preparedness

Performance Testing

Method	Glass Substrate	Film Attachment	Rating					
Safety Glazing								
16 CFR 1201	1/4" annealed		Category 2, 400 ft-lbs					
ANSI Z97.1	74 annealeu		Class A (Unlimited), 400 ft-lbs					
Impact Resistance								
ASTMs E1886 / E1996	NA							
Blast Mitigation			Blast Load	Rating				
GSA TS01-2003 / ASTM F1642	NA							
A011VI 1 104Z								

Glazing systems vary. Contact 3M for more information.

Film Properties (nominal)

-		· ·					
Film Thickness	8 mils						
Film Construction	Laminated conventional PET						
Tensile Properties (ASTM D882)							
Tensile Strength	Tensile Strength 23,000 psi (MD) / 33,000 ps						
Break Strength	170 lb/in	(MD) / 280 lb/in (TD)					
Elongation at Break	100%	6 (MD) / 80% (TD)					
Yield Strength	>12,000 psi (MD)						
Elongation at Yield		>3%					
Modulus	580 kps	i (MD) / 615 kpsi (TD)					
Abrasion Resistance (ASTM	+3% ∆ Haze						
Peel	4.5 lb/in						
Flammability (AS)	Class A						
Peel	4.5 lb/in						

Solar Properties – film applied to 1/4" glass								
	1/4" Clear	1/4" Tint	Dual Clear	Dual Tint				
VLT	38%	22%	34%	20%				
VLR-Int	13%	12%	14%	13%				
VLR-Ext	21%	10%	25%	12%				
SHGC	0.45	0.40	0.51	0.39				
TSER	55%	60%	49%	61%				
UV Block	99%	99%	99%	99%				
Glare ↓	58%	65%	52%	61%				
U-Value	1.00	1.03	0.48	0.47				
Solar Heat ↓	45%	36%	27%	23%				

Health and Safety

IMPORTANT NOTICE:

This product is **not approved** in the State of Florida for use as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm. In compliance with Florida Statute 553.842, this product may not be advertised, sold, offered, provided, distributed, or marketed in the State of Florida as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm.

The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M

Commercial Solutions Division

3M Center, Building 220-12E-04 St. Paul, MN 55144 3M.com/windowfilm

© 3M 2020. All rights reserved.

3M is a trademark of 3M. Used under license in Canada.

All other trademarks are property of their respective owners. Revision B, December 2020. Please recycle.



When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to <u>3M.com/SDS</u>, or by mail or in case of an emergency, call 1-888-364-3577 or 1-651-737-6501. When using any equipment, always follow the manufacturers' instructions for safe operation.

Technical Information

Technical information and data, recommendations, and other statements provided by 3M are based on information, tests, or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. The typical values shown should not be used for the purpose of specification limits. If you have questions about this Product, contact the Customer Service Department at 1-800-852-9722.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty

3M warrants that each 3M product will be free from defects in material and manufacture for the length of the product warranty. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Limited Remedy

If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

No Extension of Warranty

In the case of an approved warranty claim, the replacement Product will carry only the remaining term of the original warranty period.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

IMPORTANT NOTICE:

This product is **not approved** in the State of Florida for use as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm. In compliance with Florida Statute 553.842, this product may not be advertised, sold, offered, provided, distributed, or marketed in the State of Florida as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm.

The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M

Commercial Solutions Division

3M Center, Building 220-12E-04 St. Paul, MN 55144 3M.com/windowfilm

© 3M 2020. All rights reserved.
3M is a trademark of 3M. Used under license in Canada.
All other trademarks are property of their respective owners. Revision B, December 2020. Please recycle.

